ROKON. The only true all-terrain vehicle on planet earth

The Rokon is available in three rugged and versatile models: TRAILBREAKER, SCOUT and RANGER. Each features Rokon's sure-footed, two-wheel drive system that gives you the ability to go anywhere. Unvielding power delivery lets you carry and tow enormous loads. All this performance comes in compact vehicles that leave a track lighter that a person's footprint.

The automatic transmission lets you concentrate on the terrain, not shifting. A choice of three speed ranges gives you awesome power at slow speeds. Simple and easy operation means safe, stable control in all types of terrain.

Front and rear racks offer sturdy storage space for your equipment. A tow bar turns back breaking jobs into simple tasks. A rear seat lets you to carry a passenger.

For more than 50 years Rokons have been used to transport riders and equipment over hostile terrain to remote locations. Rokon takes pride in manufacturing a rugged and versatile vehicle. Long-life construction and low maintenance guarantees that your Rokon will last for many years to come.



Power Take Off Kit Power Take Off Kit operates pumps and generators in the field.



Side Car Side car attaches with just one bolt and weighs only 70 lbs.



Windshield Windshield protects against oncoming elements.



Brush Busters Brush Busters protect hands and brake levers



Log Skidder Log Skidder hauls logs up to 20" in diameter



Game Carrier/ **Gun Boot**

For hunters, a game carrier replaces the rear seat. A full gun boot is available.



TRAIL-BREAKER

Tow Bar Kit Soft or hard mount



Trail Maintenance Kit Kit Includes survival items packed into a leather pouch engraved with the Rokon name



Aluminium **Drum Wheel**

Sealed aluminium wheel housings available in 12" or 15" diameters. Allows for floatation or for storage of fuel or water.



Universal Holder



Universal Holder mount a GPS, Cell or Satellite phone and adjust for a variety of angles.



RANGER

Tire Chains Tire chains facilitate easy travel in snow

or on ice.



Trailer Rugged trailer tows heavy oads. It features a tilt box and removable tailgate.



Auto-Grab

A new Rokon option, front suspension to cushion the ride.

Tach/Hourmeter

Keep track of rpms

and engine service



SCOUT"

Wheel Free Carrier Wheel Free carrier transports the Rokon using a 2" receiver hitch.



ACT Radial Tire Aggressive tread for Soft

Sand, Snow and Mud. Size: 8.0 x 12 x 25

ROKON Sport Caps

Available in Camo or Red with embroidered ROKON logo.





Drive System	Full time, front and rear wheel drive
Engine	Kohler, single cylinder, four stroke, fan coo
Piston Displacement	172cc
Power Output	6.6 HP at 4,000 RPM
Power Transmission	Automatic torque converter into a three gear range selector
Speed Range	1st gear 0-10 MPH (16 kph) 2nd gear 0-22 MPH (35 kph) 3rd gear 0-40 MPH (64 kph)
Power Take Off	6.6 HP (est.), speed proportional to throttle setting
Fuel Tank Capacity	2.69 US gal (10.0 L)
Fuel	Regular unleaded gas
Fuel Consumption	0.45 gal/hr (1.7L per hour)
Brakes	Disc type, front and rear, dual handlebar mounted controls
Starter	Automatic recoil, Optional Electric Start
Ignition	Electronic magneto
Electrical	12 volt with 90 watt alternator
Exhaust	Muffler and US Forestry approved spark arrestor
Carburetor	Fixed main jet carburetor
Air Filter	Dry type, with foam secondary stage
Grade Capability	60 percent
Weight	208 lbs. (94.3 kg) dry weight
Warranty	12 month Limited Warranty

Dimensions

Wheels	15" aluminum drums (12" optional, overall ground clearance reduced by 1")
Tires	5.90 x 15 or 8.0 x 12 tubeless
Wheel Base	51 inches (129.5 cm)
Ground Clearance	15 inches (38.1 cm)
Height Over Seat	30 inches (76.2 cm)
Height Over Handlebar	42 inches (106.7 cm)
Width	31 inches (78.7 cm)
Length	79 inches (200.7 cm)
Fordable Water Depth	24 inches (61 cm)





Drive Syst

Engine

Piston Dis Power Ou Power Tra Speed Ra

Power Ta Fuel Tank

Fuel Cons

Brakes Starter

Ignition Electrical Exhaust

Carbureto

Air Filter

Grade Ca

Weight

Warranty

Wheels

Tires Wheel Base

Width

Length

Ground Clearance

Height Over Seat

Height Over Handlebar

Fordable Water Depth

Fuel

tem	Full time, front and rear wheel drive
	Honda, single cylinder, four stroke, fan cooled
splacement	160cc
itput	5.5 HP at 3,900 RPM
ansmission	Automatic torque converter into a three gear range selector
inge	1st gear 0-10 MPH (16 kph) 2nd gear 0-20 MPH (32 kph) 3rd gear 0-30 MPH (48 kph)
ke Off	5.5 HP (est.), speed proportional to throttle setting
Capacity	2.69 US gal (10.0 L)
	Regular unleaded gas
sumption	0.36 gal/hr (310 g/Kwh, 230 g/Hh)
	Disc type, front and rear, dual handlebar hydraulic mounted controls
	Automatic recoil, Optional Electric Start
	Electronic magneto
	12 volt with 90 watt charging system
	Muffler and US Forestry approved spark arrestor
or	Fixed main jet carburetor
	Dry type, with foam secondary stage
pability	60 percent
	228 lbs. (103.4 kg) dry weight
	12 month Limited Warranty

Dimensions


	12 inch steel spoke (optional 15" spoke wheel)
	8.0 x 12 tubeless
	51 inches (129.5 cm)
	14 inches (36 cm),15" with 15" spoke wheel
	31 inches (79 cm) 32" with 15" spoke wheel
r	41 inches (104 cm) 42" with 15" spoke wheel
	29 inches (74 cm)
	77 inches (196 cm)
	23 inches (58 cm) or 24" with 15" spoke wheel





Drive Syster	n	Full time, front and rear wheel drive
Engine		Kohler, single cylinder, four stroke, fan cooled
Piston Displ	acement	172cc
Power Outp	ut	6.6 HP at 4,000 RPM
Power Trans	mission	Automatic torque converter into a three gear range selector
Speed Rang	je	1st gear 0-10 MPH (16 kph) 2nd gear 0-22 MPH (35 kph) 3rd gear 0-40 MPH (64 kph)
Power Take	Off	6.6 HP (est.), speed proportional to throttle setting
Fuel Tank Ca	apacity	2.69 US gal (10.0 L)
Fuel		Regular unleaded gas
Fuel Consur	nption	0.45 gal/hr (1.7L per hour)
Brakes		Disc type, front and rear, dual handlebar mounted controls
Starter		Automatic recoil, Optional Electric Start
Ignition		Electronic magneto
Electrical		12 volt with 90 watt alternator
Exhaust		Muffler and US Forestry approved spark arrestor
Carburetor		Fixed main jet carburetor
Air Filter		Dry type
Grade Capa	bility	60 percent
Weight		228 lbs. (103.4 kg) dry weight
Warranty		12 month Limited Warranty
Dimensions		
Wheels		12 inch steel spoke (optional 15" spoke wheel)

Wheels	12 inch steel spoke (optional 15" spoke wheel)
Tires	8.0 x 12 tubeless
Wheel Base	51 inches (129.5 cm)
Ground Clearance	14 inches (36 cm),15" with 15" spoke wheel
Height Over Seat	31 inches (79 cm) 32" with 15" spoke wheel
Height Over Handlebar	41 inches (104 cm) 42" with 15" spoke wheel
Width	29 inches (74 cm)
Length	77 inches (196 cm)
Fordable Water Depth	23 inches (58 cm) or 24" with 15" spoke wheel



D





TRAIL-BREAKER. **RANGER** SCOUT





